


## Harlequin Activity with Vinyl Surfaces

A polymer damp-proof membrane is laid across the subfloor onto which is placed a layer of cellular polyurethane of proprietary density. Two layers of semi-flexible panels are then installed. Then the selected Harlequin vinyl performance surface is installed and adhered. The seams are welded to form an unbroken surface and, finally, the gap between the flooring and the wall is filled with a composite skirting profile.


### Specification Guide Harlequin Activity with Vinyl Surface

Overall Thickness	2" (52mm) nominal, depending on vinyl surface specified
Weight	37-40 lbs/yd <sup>2</sup> (20-25kg/m <sup>2</sup> ) depending on surface specification

Depending on individual performance requirements, the following are suitable as the top performance surface of an Activity Floor:



Cellular polyurethane layer      First layer of semi-flexible panels      Top semi-flexible panel layer with joints staggered      Harlequin vinyl performance surface



HARLEQUIN ACTIVITY is a permanently installed sprung floor system based on the now well-established triple sandwich construction originated by Harlequin over 20 years ago. It is a fully-floating system with no fixings to the sub-floor, and can be laid on almost any reasonably smooth flat, dry surface without preparation.

**American Harlequin Corporation**  
1531 Glen Avenue  
Moorestown, NJ 08057, USA  
Tel. (856) 234 5505  
Toll Free (800) 642 6440  
Fax (856) 231 4403  
www.harlequinfloors.com  
dance@harlequinfloors.com

**British Harlequin plc**  
Festival House, Chapman Way  
Tunbridge Wells, Kent TN2 3EF  
England  
Tel. +44 (0)1892 514 888  
Fax +44 (0)1892 514 222  
Freephone 0800 28 99 32  
www.harlequinfloors.com  
enquiries@harlequinfloors.com

**Harlequin Europe S.A**  
29, rue Notre-Dame  
L-2240 Luxembourg  
Tel. (+352) 46 44 22  
Tel. FR (+352) 46 44 99  
Tel. DE (+352) 46 39 39  
Fax (+352) 46 44 40  
www.harlequinfloors.com  
info@harlequinfloors.com

**Harlequin Australasia Pty Ltd.**  
PO Box 1028, 36A Langston Place  
Epping, NSW 1710, Australia  
Tel. +61 (2) 9869 4566  
Fax +61 (2) 9869 4547  
AUS Freecall 1300 666 900  
www.harlequinfloors.com  
contact@harlequinfloors.com

Philadelphia  
London  
Paris  
Los Angeles  
Sydney  
Luxembourg  
Fort Worth  
Hong Kong

## Harlequin Activity with Hardwood Surface

The construction is identical to Activity with a Harlequin vinyl surface, but the vinyl is replaced by a selected hardwood surface layer.


The hardwood surface may optionally be protected by impregnation with a multi-coat hardwearing polymer lacquer. The expansion gap around the perimeter of the room can be concealed by an optional scotia profile of matching hardwood to form a neat edging.

### Specification Guide Harlequin Activity with Hardwood Surface

Overall Thickness	2 <sup>1</sup> / <sub>4</sub> " nominal (57mm)
Description of Board	1/2" (13mm) - 3/4" (19mm) hardwood
Weight	47-50lbs/yd <sup>2</sup> (17-19kg/m <sup>2</sup> ) depending on hardwood surface chosen
Laying Time	A floor of 120-180yd <sup>2</sup> (100-150m <sup>2</sup> ) can generally be installed in 5 days



New Activity Floor with maple surface



Installing the hardwood onto the support layer for the Crystal Cruise Line's ship, Crystal Serenity.



**HARLEQUIN**  
The world dances on Harlequin floors®

Sprung Floor System

## HARLEQUIN ACTIVITY®

### Harlequin Activity with Vinyl & Hardwood Surfaces

Harlequin Activity is a permanently installed sprung floor system based on the now well-established triple sandwich construction originated by Harlequin over 20 years ago. It is a fully-floating system with no fixings to the sub-floor and can be laid on almost any reasonably smooth and flat surface without preparation.

The construction of Harlequin Activity is shock-damped to avoid a 'trampoline' effect and provides area elasticity to offer identical characteristics across the whole floor. Correctly reinforced, Harlequin Activity can withstand heavy loading including retractable seating. Harlequin Activity has been tested for impact sound reduction with a variety of different Harlequin surfaces, according to BS EN ISO 140-8; 1998. The excellent results achieved ranged from 22 to 24dB.

Harlequin Activity can be installed with a choice of surfaces:

- Harlequin vinyl surface: for all types of dance, but particularly ballet.
- Hardwood surface: for specifiers who need a hardwood surface for multi-purpose use, including traffic by the general public, full stage entertainment, ballroom dance, or even for designers obliged to match existing decor.

Harlequin Activity floor is only available for installation by Harlequin's Contracts Division.



Harlequin Activity Floor with Cascade surface at Dance Barn, National Dance Institute of New Mexico



Photography by:  
In Sight Foto

2.2 Harlequin Activity

2.2 Harlequin Activity

01/08/AH022

DISTRIBUTOR



**HARLEQUIN**  
The world dances on Harlequin floors®



### Application Guide - Harlequin's Portable & Permanent Vinyl Floors

Available

REVERSIBLE	STUDIO	STUDIO 'B'	CASCADE	ALLEGRO	TEMPO	FIESTA	STANDFAST	MARINE
------------	--------	------------	---------	---------	-------	--------	-----------	--------

**Liberty Permanent**

**Liberty Portable**

**Activity**

**WoodSpring**



### DIN Standard 18032 Part II Test Results Harlequin Activity

	Shock Absorption	Vertical Deformation	Area Deflection	Rolling Load
Requirement	Min 53%	Min 2.3mm	Max 15%	Min 1500 N
Harlequin Activity	59.4%	3.8mm	7.2%	> 1500 N

CONTACT US FOR SAMPLES ON TOLL FREE (800) 642 6440

The Company reserves the right to make any variation in design or construction of the material described.

#### Guarantee

Harlequin™ and Activity® are trademarks of British Harlequin plc, American Harlequin Corporation and Harlequin Europe SA.

Country of origin: Made in the US © British Harlequin plc, American Harlequin Corporation and Harlequin Europe SA. 2008